

Sliding table saw

minimax sc 4e 33

With swiveling saw blade and anodised aluminum format sliding carriage for the discerning user



Article number ▾

5504534

Brand ▾

Holzkraft

Availability ▾

No stock available

Information:

Next availability

Expected on calendar week 10/2024



Catalog directory ▾

Woodworking machinery » Circular saw / Sliding table saws » Sliding table saws » minimax sc 4e


Purchase ▾

Minimum 1 pc(s).

Shipping informations ▾

Packaging Metrics		Weights		Delivery		Other	
Length	7,240 mm	Gross	489 kg	Delivery	Carrier	DualUse	✘
Width	4,410 mm	Net	489 kg	Content	1 pc(s).	SCIP	n/a
Height	900 mm					SVHC	No

Root data ▾

Country of origin	EAN	Custom number	Quantity unit
 Italy	4036351221159	84659120	pc(s).



MADE IN ITALY

Description ▾

- The solid work table made of heavily ribbed grey cast iron and the base frame made of welded steel warranty high torsional stiffness and vibration-free work
- Smooth-running and precise sliding carriage made of anodized aluminium with proven and permanently smooth-running ball contact system on hardened, 10-year warranty on wear of the guideways
- Cast iron saw unit with permanently precise double swivel segment guide and zero-point swivel, 6 years Holzskraft warranty on wear of the swivel segments
- Equipped with powerful three-phase motor
- Saw blade tilting is indicated on a scale on the unit
- Large edging frame with roller facilitates panel feeding
- Angle-adjustable aluminium telescopic fence with two professional folding fences
- Folding rip fence with quick clamping and fine adjustment
- Standard with table extension, table extension and eccentric clamp
- Made in Italy

Significant Features ▼



Media informations ▼



Aluminium sliding table

- Equipped with thousandfold proven ball contact system
- Permanently smooth running
- Insensitive to dust and dirt due to minimal contact point between ball and trapezoidal rail
- 10 years Holzskraft warranty on wear of the guideways



Sawing unit with double swivel segment guide

- Durable precision due to double swivel segment guide
- 6-year Holzkraft warranty on wear of the swivel segments



Degree display

- Easy to read degree display for saw blade tilt
- Accurate to the tenth




Rip fence with round bar guide

- With fine adjustment and quick clamping
- Stable round bar guide made of ground steel with 45 mm diameter
- Foldable as standard for cutting large workpieces to size



Cast iron double weigh saw unit

- Height adjustment via dovetail guide
- Extremely robust and torsion-resistant for precise cuts
- Close to the saw blade, mounted on both sides
- Height and up to 45° inclination adjustable
- Illustration shows optionally available scoring device with drive via separate motor



100% cutting height

- Maximum cutting height is achieved even with pre-scoring device installed
- Optionally with separate scoring motor

Technical data ▼







Dimensions and weights			
Net weight approx.	489 kg		
Extraction port			
Extraction port diameter bottom	120 mm	Saw blade protection extraction port diameter	60 mm
Footprint			
Transport width	980 mm	Length	1900 mm
Width/depth	840 mm	Space requirement length	7235 mm
Space requiremen width/depth	44 – 10 mm	Explanation about space requirement The dimensions take into account maximum travel distances or usable lengths	
Work area length	1600 mm	Work area width/depth	2300 mm
Explanation about work area	Please add the given dimensions with the required space to obtain the free space recommended for the machine.		
Electrical Data			
Supply voltage	400 V	Mains frequency	50 Hz
Drive motor output	5.0 kW	Duty type drive motor	S6
Duty cycle drive motor	40 %		
Sliding carriage and table			
Sliding carriage length	3200 mm	Sliding carriage width	360 mm
Sliding carriage height	142 mm	Table length	840 mm
Table width	560 mm	Work height	900 mm
Circular saw unit			
Max. cutting width with rip fence	900 mm		

		Max. cross cut width left from saw blade	3200 mm
Trimming length	3260 mm	Saw blade angle	90 – 45 °
Max. cutting height 90°	100 mm	Max. cutting height 45°	70 mm
Explanation to: Max. cutting height	Independent of the scoring unit	(Main) saw blade diameter	315 mm
Explanation to: (Main) saw blade diameter	Independent of the scoring unit	(Main) saw blade speed	3800 min ⁻¹
Pre-scoring unit			
Diameter scoring saw blade	100 mm	Scoring saw blade speed	8000 min ⁻¹

Equipment ▼

Anodised aluminium sliding sizing carriage	✓	Handle for sliding carriage	✓
Material roll on claming frame	✓	Saw rip fence	with round rod guide
Stops	Two professional folding stops	Clamp sleigh	✓
Eccentric clamp	✓	Table broadening	✓
Table lengthening	✓	Saw blade cover	✓

Accessories ▼

	Extraction system connection set 120/58 mm		
Article number ▼	Availability ▼	Purchase ▼	Price informations ▼
5146060	In stock Immediate delivery	Minimum 1 pc(s).	
	Extraction system connection set 120/80 mm		
Article number ▼	Availability ▼	Purchase ▼	Price informations ▼
5146080	Small stock amount Article available	Minimum 1 pc(s).	
	Blade guard PSH		
Article number ▼	Availability ▼	Purchase ▼	Price informations ▼
5510404	No stock available Information: Next availability Expected on calendar week 09/2024	Minimum 1 pc(s).	



Mitre fence 1060 mm, with telescopic guide




Article number ▼
5514315

Availability ▼
No stock available
Information:
Next availability
Expected on
calendar week
14/2024

Purchase ▼
Minimum 1 pc(s).

Price informations ▼

Options equipment ▼



Digital display of the working width at the rip fence PA-DIGI-UNI



Article number ▼
5516000

Availability ▼
No stock available
Information:
Next availability
Expected on
calendar week
09/2024

Purchase ▼
Minimum 1 pc(s).

Price informations ▼



Angle cutting device with grid division




Article number ▼
5510399

Availability ▼
In stock
Immediate delivery

Purchase ▼
Minimum 1 pc(s).

Price informations ▼



Pre-cutting device with separate motor, saw blade 100 mm



Article number ▼
5510401

Availability ▼
No stock available
Information:
Next availability
Unknown

Purchase ▼
Minimum 1 pc(s).

Price informations ▼

Prices on this data sheet are recommended retail prices, subject to change, in €, plus VAT at the statutory rate, plus packaging, shipping, transport, unloading, assembly and, if applicable, instruction costs. Sales prices of the dealers can deviate. No liability is accepted for printing errors, mistakes or incorrect presentation. Technical and optical changes are reserved. Illustration partly with optional accessories.