

Table saw

TKS 316 PRO (230 V)

Stable circular saw for precise work



Article number ▼

5902321

Brand ▼

Holzstar

Availability ▼

In stock
Immediate delivery

Catalog directory ▼

Woodworking machinery » Circular saw /
Sliding table saws » Table Saws

Purchase ▼

Minimum 1 pc(s).




Delivery content ▼

- Chassis
- Sliding sleighs
- Table extension tat, 800 x 550 mm
- Rip fence
- HM saw blade 315 mm/36 Z
- Saw blade cover with suction hose
- Miter fence without aluminium profile (profile available as accessories)

Shipping informations ▼

Packaging Metrics		Weights		Delivery		Other	
Length	100 mm	Gross	67 kg	Delivery	Carrier	DualUse	✘
Width	1,000 mm	Net	60 kg	Content	1 pc(s).	SCIP	n/a
Height	620 mm					SVHC	No

Root data ▼

Country of origin	EAN	Custom number	Quantity unit
 China	4036351275398	84659120	pc(s).

Description ▼

- Large machine table made of galvanized steel
- Standard table extension can also be mounted as table widening right
- Precise sawmill swing over hand wheel with scale
- Saw blade height adjustable via easy-to-reach hand wheel
- Precise cuts due to stable, double suspension of the sawing unit
- Rip fence allows the lining of boards, thicknesses, fiber and angle cuts
- Easily drivable through integrated landing gear and foldable transport handles
- For easy transport or space-saving storage table feet can be folded easily

Media informations



Illustration shows miter fence with aluminum profile,
profile available as accessories





- Sliding sled ball stored
- Includes continuously from -45 ° to 45 ° adjustable meter fence
- Fixation of the stop with quick clamp lever
- Breeding attack without aluminum profile, profile available as accessories



- The parallel fence with eccentric rapid clamp can be adjusted precisely and easily on a scale.



- With accurate and smooth height and sloping adjustment of the sawing unit by easy-to-use hand wheels.



- Additional table 800 x 550 mm included
- Suitable as a table extension and widening



Technical data ▼

Dimensions and weights			
Length (product) approx.	1350 mm	Width/depth (product) approx.	1250 mm
Height (product) approx.	1000 mm	Net weight approx.	60 kg
Extraction port			
Extraction port diameter bottom	100 mm	Saw blade protection extraction port diameter	30 mm
Electrical Data			
Supply voltage	230 V	Mains frequency	50 Hz
Absorbed power drive motor	2,2 kW	Delivery power	1.6 kW
Total rated value	10.3 A	Motor speed	2800 min ⁻¹
Sliding carriage and table			
Table length	800 mm	Table width	550 mm
Work height	850 mm		
Circular saw unit			
Max. cutting width with rip fence	200 mm	Max. cross cut width left from saw blade	245 mm
Saw blade angle	90 – 45 °	Max. cutting height 90°	90 mm
Max. cutting height -45°	50 mm	(Main) saw blade diameter	315 mm
(Main) saw blade speed	2800 min ⁻¹		

Accessories ▼



Mitre gauge WA-TKS316PRO

Article number ▼
5912323

Availability ▼
In stock
Immediate delivery

Purchase ▼
Minimum 1 pc(s).

Price informations ▼





Aluminium profile for miter gauge



Article number ▼
5912322

Availability ▼
In stock
Immediate delivery

Purchase ▼
Minimum 1 pc(s).

Price informations ▼



Cut-to-size alternating teeth circular saw blade KSB-WZ 315/28



Highest quality level especially for industrial applications on stationary machines

Article number ▼
5263128

Availability ▼
In stock
Immediate delivery

Purchase ▼
Minimum 1 pc(s).

Price informations ▼



Additional table extension right 800x550mm



Article number ▼
5912321

Availability ▼
In stock
Immediate delivery

Purchase ▼
Minimum 1 pc(s).

Price informations ▼

Prices on this data sheet are recommended retail prices, subject to change, in €, plus VAT at the statutory rate, plus packaging, shipping, transport, unloading, assembly and, if applicable, instruction costs. Sales prices of the dealers can deviate. No liability is accepted for printing errors, mistakes or incorrect presentation. Technical and optical changes are reserved. Illustration partly with optional accessories.